



KESKKÜTTE PUHURID



MUDEL		WH 50-4	WH 80-4	WHT 30	WHT 45
Soojustusvõimsus:	max. kW	42,6	68,7	25,2	42,6
Õhukogus:	m ³ /h	3000	4500	2000	4000
Vee temperatuur:	max C	130	130	130	130
Müratase:	dB	75	70	68	69
Kaal:	kg	57	72	65	80



MUDEL	PWW	30-4	50-4
Võimsus 90/70 °C	max. kW	33,2	59,9
Õhukogus	m ³ /h	1450/1800	2640/3040
Vee temperatuur:	max C	130	130
Müratase:	dB	50/57	56/60
Kaal:	kg	27	36

NIISKUSEKOGUJAD

ETF 220



REMKO niiskusekogujad	ETF 220	AMT 30	AMT 50	AMT 60E	AMT90E	
Kasutamistemperatuur:	°C	6-32	3-32	3-32	3-32	
Jõudlus:	l/24h	22	30	50	64	93
Õhukogus:	m ³ /h	150/190	350	650	765	1050
Kaal:	kg	21	36	50	48	63



AMT 30 ja 50



60E/90E

REMKO niiskusekogujad	LAF 50	LAF100	LAF 150	
Kasutamistemperatuur:	°C	3-32	3-30	3-30
Jõudlus:	l/24h	24	44	65
Õhukogus:	m ³ /h	550	850	900
Kaal:	kg	38	52	63

LAF 50; 100; 150

